

Technical Data easyTone

EASYTONE SPECIFICATIONS

Test Signals	Pure tone and warble tone (steady and pulse)
Test Frequencies	125, 250, 500, 750, 1000, 1500, 2000, 3000, 4000, 6000, 8000 Hz
Level Steps	5 dB
Hearing Level Range AC	-10 dB HL to 100 dB HL
Language	English, French, German, Hungarian, Korean, Polish, Spanish, Turkish
Result Display Type	Table and audiogram

EASYTONE AUDIOMETER HEADPHONE

Dimensions	W x D x H: 19.1 cm x 9.3 cm x 13.4 cm
Weight	389 g
Power Supply	via USB
Output	USB-C®
Input	Patient response switch
Noise Monitor	Built-in microphone

TABLET SPECIFICATIONS

Resolution	2000 x 1200 pixel
Screen Size	10.6"
Operating System	Android™
Version	13
Input	USB-C®

COMPANION SOFTWARE - SYSTEM REQUIREMENTS

Display Requirements	1280 x 960 resolution
Operating System	Windows® 11 64 Bit Windows® 10 Pro, Enterprise 64 Bit (No „N“ Edition) macOS Monterey

STANDARDS

Audiometer	IEC 60645-1 Type 4 ANSI/ASA S3.6 Type 4 CAN/CSA-C22.2 No. 60601-1
Safety	IEC 60601-1 ANSI/AAMI ES60601-1 Type B applied parts
EMC	IEC 60601-1-2
CE 0123	Class IIa according to Medical Device Regulation (EU) 2017/745

Specifications are subject to change without notice.