

MA 1

Super-Lightweight Hearing Screener

Small and Handy

With its super-lightweight design the MA 1 is small enough to fit in the palm of your hand. MA 1 is our lightest and most handy air conduction hearing screener. Frequencies and intensities can be presented by one hand operation.

Ideal for Fast Screening Purposes

The device is capable delivering a pure tone signal to one ear at a time. The stimulus range is 15 to 50 dB HL in level steps of 5 dB. Test Frequencies range from 500 to 4000 Hz. The unit is equipped with the AC headphone DD45.

If the MA 1 is used in noisy environment, we recommend to choose the optional AC noise-enclosure headphone DD65 v2.

Extended Battery Life

The MA 1 is powered by 2 AA alkaline batteries. The unit turns off automatically when inactive and turns on again when pressing any of the 7 buttons.

Features at a Glance

- Handheld air-conduction screener
- Easy one hand operation
- Exceptionally lightweight
- Test frequencies: 500, 1000, 2000 and 4000 Hz
- Pure tone signal from 15 dB HL to 50 dB HL
- Battery operated (2 AA batteries)
- Automatic power off
- AC headphone DD45
- Optional AC noise-enclosure headphone DD65 v2



Technical Data

MA 1 SPECIFICATIONS

Test Signals	Pure tone (continuous)
Test Frequencies	500, 1000, 2000, 4000 Hz
Level Steps	5 dB
Hearing Level Range AC	15 dB HL to 50 dB HL
Accuracy	± 4 dB
Distortion	less than 3 %

DEVICE GENERAL

Dimensions	W x D x H: 6.4 cm x 15.3 cm x 2.3 cm
Weight	115 g (device and batteries only)
Power Supply	2 AA batteries
	Automatic power off
Battery Life	6 months, depending on the battery self-discharge

STANDARDS

Safety	IEC 60601-1: 2012 Type B applied parts
EMC	IEC 60601-1-2:2014
CE 0123	Class IIa according to Medical Device Regulation (EU) 2017/745
Audiometer	The MA 1 is not classified according to the standard EN 60645-1 and is not in conformity with this standard.

STANDARD COMPONENTS

- AC headphone DD45
- Device cradle
- 2 AA batteries

OPTIONAL TRANSDUCER

AC noise-enclosure headphone DD65 v2


Specifications are subject to change without notice.



Standard Components



MA 1 handheld device



AC Headphone DD45

Optional Transducer



AC headphone DD65 v2

MAICO Diagnostics GmbH

Sickingenstr. 70-71 · 10553 Berlin · Germany
 Tel.: +49 30 / 70 71 46-50 · Fax: +49 30 / 70 71 46-99
 sales@maico.biz · www.maico.biz



Find you nearest Distributor.

